



State of Idaho
Department of Environmental Quality
Air Quality Division

**AIR QUALITY PERMIT
STATEMENT OF BASIS**

Permit to Construct No. P-2008.0013

Final

Western Aircraft Inc.

Boise, Idaho

Facility ID No. 001- 00220

June 12, 2008

Almer Casile *ABC*

Permit Writer

The purpose of this Statement of Basis is to satisfy the requirements of IDAPA 58.01.01.200, Rules for the Control of Air Pollution in Idaho, for issuing air permits.

Table of Contents

| | |
|--|----|
| ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURE | 3 |
| 1. FACILITY INFORMATION | 4 |
| 2. APPLICATION SCOPE | 4 |
| 3. TECHNICAL ANALYSIS..... | 4 |
| 4. REGULATORY REVIEW | 5 |
| 5. PERMIT FEES | 7 |
| 6. PUBLIC COMMENT | 8 |
| APPENDIX A – AIRS INFORMATION | 9 |
| APPENDIX B – EMISSIONS INVENTORY | 11 |
| APPENDIX C – MODELING ANALYSIS..... | 17 |

Acronyms, Units, and Chemical Nomenclature

| | |
|-------------------|--|
| acfm | actual cubic feet per minute |
| AFS | AIRS Facility Subsystem |
| AIRS | Aerometric Information Retrieval System |
| AQCR | Air Quality Control Region |
| ASTM | American Society for Testing and Materials |
| BACT | Best Available Control Technology |
| Btu | British thermal unit |
| CAA | Clean Air Act |
| CFR | Code of Federal Regulations |
| CO | carbon monoxide |
| DEQ | Department of Environmental Quality |
| gr | grain (1 lb = 7,000 grains) |
| dscf | dry standard cubic feet |
| EPA | U.S. Environmental Protection Agency |
| gpm | gallons per minute |
| HAPs | Hazardous Air Pollutants |
| hp | horsepower |
| IDAPA | a numbering designation for all administrative rules in Idaho promulgated in accordance with the Idaho Administrative Procedures Act |
| km | kilometer |
| lb/hr | pound per hour |
| m | meter(s) |
| MACT | Maximum Achievable Control Technology |
| MMBtu | million British thermal units |
| NESHAP | National Emission Standards for Hazardous Air Pollutants |
| NO ₂ | nitrogen dioxide |
| NO _x | nitrogen oxides |
| NSPS | New Source Performance Standards |
| PC | permit condition |
| PM | particulate matter |
| PM ₁₀ | particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers |
| ppm | parts per million |
| PSD | Prevention of Significant Deterioration |
| PTC | permit to construct |
| PTE | potential to emit |
| Rules | Rules for the Control of Air Pollution in Idaho |
| scf | standard cubic feet |
| SIC | Standard Industrial Classification |
| SIP | State Implementation Plan |
| SM | Synthetic Minor |
| SO ₂ | sulfur dioxide |
| SO _x | sulfur oxides |
| T/yr | tons per year |
| µg/m ³ | micrograms per cubic meter |
| UTM | Universal Transverse Mercator |
| VOC | volatile organic compound |

STATEMENT OF BASIS

| | | |
|-------------------|----------------------|-----------------------------------|
| Permittee: | Western Aircraft Inc | Permit No.: P-2008.0013 |
| Location: | Boise, Idaho | Facility ID No. 001- 00220 |

1. FACILITY INFORMATION

1.1 Facility Description

Aircraft Interior refurbishment (refinishing cabinets and recovering walls and headliners with fabric)

1.2 Permitting History

This permitting action involves the issuance of the initial PTC for this facility.

2. APPLICATION SCOPE

This permitting action involves installation of a two station spray booth and a prep area.

2.1 Application Chronology

| | |
|--|---|
| February 12, 2008 | DEQ received application and application fee. |
| March 11, 2008 | DEQ determined application complete. |
| February 22, 2008 to March 10, 2008 | Opportunity for public comment period started. Opportunity of public comment period ended. |
| April 17, 2008 | DEQ sent facility review permit to facility. |
| May 3, 2008 | Public comment period started. |
| June 2, 2008 | Public comment period ended. |

3. TECHNICAL ANALYSIS

Table 3.1 EMISSION UNIT AND CONTROL DEVICE INFORMATION

| Emissions Unit / Process | Emissions Control Device | Emissions Point |
|---------------------------|--|-----------------|
| Spray Booth (Two-Station) | Two Stage Filter System. Stage 1 Filter with Control Efficiency of 96.5% Stage 2 Filter with Control Efficiency of 99.1% | Stack 1 |
| | Two Stage Filter System. Stage 1 Filter with Control Efficiency of 96.5% Stage 2 Filter with Control Efficiency of 99.1% | Stack 2 |

3.2 Emissions Inventory

An emissions inventory was submitted by the permittee. The emissions estimates contained in Table 3.2 are based on the worst case PM₁₀, VOC, and HAP emissions for all coating listed in the application. All emission rates are based on 654 hours/year of operation. The HAP emission rate in Table 3.2 represents worst case emission rate for material sprayed by one spray gun for 654 hours per 12 consecutive month period. The worst case emission rate for any individual HAP contained in material sprayed by one spray

STATEMENT OF BASIS

| | | |
|-------------------|----------------------|-----------------------------------|
| Permittee: | Western Aircraft Inc | Permit No.: P-2008.0013 |
| Location: | Boise, Idaho | Facility ID No. 001- 00220 |

gun for 654 hours per 12 consecutive month period was 3.09 T/yr. PM₁₀ emission estimates were determined using the spray booth filter efficiency and spray gun application efficiency of 99% and 65%, respectively. Sample calculations and the applicant's emissions inventory are contained in Appendix B.

Table 3.2 EMISSIONS ESTIMATES

| Emissions Unit | PM ₁₀ | | VOC | HAP |
|--|------------------|------|------|------|
| | lb/hr | T/yr | T/yr | T/yr |
| Point Sources Affected by the Permitting Action | | | | |
| Spray Booth | 0.03 | 0.01 | 6.72 | 3.38 |
| Total, Point Sources | 0.03 | 0.01 | 6.72 | 3.38 |

The emissions estimates contained in Table 3.3 are based on the worst case TAP emissions for all coatings listed in the application. All emission rates are based on 654 hours of operation per year.

Table 3.3 TAP AND HAP EMISSIONS SUMMARY

| TAPS | HAPS | Screen Level | 24-hour Average ^a | Annual Average ^a |
|---------------------|---------------|--------------|------------------------------|-----------------------------|
| | | lb/hr | lb/hr | lb/hr |
| Butyl Acetate | | 47.3 | 6.3 | N/A |
| Acetone | | 119 | 5.6 | N/A |
| Methyl Ethyl Ketone | | 39.3 | 2.43 | N/A |
| Hexane | Hexane | 12 | 5.54 | N/A |
| Toluene | Toluene | 25 | 9.46 | N/A |
| Xylene | Xylene | 29 | 1.63 | N/A |
| Ethyl Benzene | Ethyl Benzene | 29 | 2.47 | N/A |

- a. 24-hour average only applies to non-carcinogenic TAPS. Annual average only applies to carcinogenic TAPS.
 b. NA = not applicable.

Ambient Air Quality Impact Analysis

The estimated emissions rate for PM₁₀ is below the modeling threshold; therefore, modeling is not required in accordance with State of Idaho Air Quality Modeling Guidance DEQ Publication, December 2002. In accordance with IDAPA 58.01.01.210.05, the uncontrolled emission rates for the pollutants listed in Table 3.3 is less than or equal to the applicable screening emission level and, therefore, no further procedures for demonstrating preconstruction compliance were required.

4. REGULATORY REVIEW

4.1 Attainment Designation (40 CFR 81.313)

The facility is located in Ada County which is designated as attainment or unclassifiable for PM₁₀, PM_{2.5}, CO, NO₂, SO_x, and Ozone. Reference 40 CFR 81.313.

4.2 Permit to Construct (IDAPA 58.01.01.201)

IDAPA 58.01.01.201 Permit to Construct Required

The facility's proposed project does not meet the permit to construct exemption criteria contained in Sections 220 through 223 of the Rules. Therefore, a PTC is required.

STATEMENT OF BASIS

| | | |
|-------------------|----------------------|-----------------------------------|
| Permittee: | Western Aircraft Inc | Permit No.: P-2008.0013 |
| Location: | Boise, Idaho | Facility ID No. 001- 00220 |

IDAPA 58.01.01.203 Permit Requirements for New and Modified Stationary Sources

The facility has shown to the satisfaction of DEQ that it will comply with all applicable emissions standards, ambient air quality standards, and toxic increments.

IDAPA 58.01.01.210 Demonstration of Preconstruction Compliance with Toxic Standards

The facility has demonstrated preconstruction compliance for all TAPs identified in the permit application.

IDAPA 58.01.01.224 Permit to Construct Application Fee

The facility satisfied the PTC application fee requirement by submitting a fee of \$1,000.00 on July 31, 2006.

IDAPA 58.01.01.225 Permit to Construct Processing Fee

The total emissions from the proposed new facility are between 10 and 100 T/yr; therefore, the associated processing fee is \$5,000.00.

IDAPA 58.01.01.585 Toxic Air Pollutants Non-Carcinogenic Increments.

The facility has demonstrated preconstruction compliance for all TAPs identified in the permit application. Any material used in the spray booth and not specifically listed in the application shall comply with this requirement.

IDAPA 58.01.01.586 Toxic Air Pollutants Carcinogenic Increments.

The facility has demonstrated preconstruction compliance for all TAPs identified in the permit application. Any material used in the spray booth and not specifically listed in the application shall comply with this requirement.

4.3 Title V Classification (IDAPA 58.01.01.300, 40 CFR Part 70)

IDAPA 58.01.01.312 Duty To Apply

The facility is not a Tier I source in accordance with IDAPA 58.01.01.006.113. Therefore, the requirements of IDAPA 58.01.01.312 do not apply.

4.4 PSD Classification (40 CFR 52.21)

40 CFR 52.21 Prevention of Significant Deterioration Of Air Quality

The facility is not a major stationary source as defined in 40 CFR 52.21(b)(1), nor is it undergoing any physical change at a stationary source, not otherwise qualifying under paragraph 40 CFR 52.21(b)(1) as a major stationary source, that would constitute a major stationary source by itself as defined in 40 CFR 52.21(b). Therefore, in accordance with 40 CFR 52.21(a)(2), the PSD requirements do not apply.

4.5 NSPS Applicability (40 CFR 60)

No NSPS apply to this facility

STATEMENT OF BASIS

| | | |
|-------------------|----------------------|-----------------------------------|
| Permittee: | Western Aircraft Inc | Permit No.: P-2008.0013 |
| Location: | Boise, Idaho | Facility ID No. 001- 00220 |

4.6 NESHAP Applicability (40 CFR 61)

40 CFR 63, Subpart GG does not apply to this facility because this permitting action establishes the facility's potential to emit below major source thresholds.

4.7 MACT Applicability (40 CFR 63)

No MACT apply to this facility because it is a minor source of HAPs.

4.8 CAM Applicability (40 CFR 64)

40 CFR 64 does not apply to this facility because it is not required to obtain a part 70 or 71 permit.

4.9 Permit Conditions Review

Permit Condition 2.3 establishes the annual emission limits for VOC, individual HAPs, and any combination of HAPs. Emission limits for individual HAPs, and any combination of HAPs were included into the permit to clearly establish the PTE for those pollutants, and clearly show that facility is below major source thresholds.

Permit Condition 2.4 establishes the opacity requirements for the 2 stacks associated with the paint booth. Permit Condition 2.5 established the odor requirements for the permittee. Permit Conditions 2.11, 2.14, and 2.15 contain the monitoring, recordkeeping and reporting requirements necessary to demonstrate compliance with the opacity requirements of Permit Condition 2.5.

Permit Condition 2.6 limits the hours of operation of the spray booth. Permit Condition 2.7 requires the permittee to operate only one spray gun at a time. Permit Condition 2.6 and 2.7 have been established to limit the PTE of VOCs, and individual and any combination of HAPS to the levels in Permit Condition 2.3. Permit Conditions 2.8 through 2.10 and 2.12 through 2.15 establish the operating, monitoring, recordkeeping, and reporting requirements necessary to demonstrate compliance with Permit Condition 2.3

5. PERMIT FEES

Table 5.1 lists the processing fee associated with this permitting action. The facility is subject to a processing fee of \$5000.00 because its permitted emissions are 10.11 TPY. This fee was received on February 13, 2008.

Table 5.1 PTC PROCESSING FEE TABLE

| Pollutant | Emissions Inventory | | |
|------------------|----------------------------------|-----------------------------------|--------------------------------|
| | Annual Emissions Increase (T/yr) | Annual Emissions Reduction (T/yr) | Annual Emissions Change (T/yr) |
| NO _x | 0.0 | 0 | 0.0 |
| SO ₂ | 0.0 | 0 | 0.0 |
| CO | 0.0 | 0 | 0.0 |
| PM ₁₀ | 0.01 | 0 | 0.01 |
| VOC | 6.72 | 0 | 6.72 |
| HAPS | 3.38 | 0 | 3.38 |
| Total: | 10.11 | 0 | 10.11 |
| Fee Due | \$5000.00 | | |

STATEMENT OF BASIS

| | | |
|-------------------|----------------------|-----------------------------------|
| Permittee: | Western Aircraft Inc | Permit No.: P-2008.0013 |
| Location: | Boise, Idaho | Facility ID No. 001- 00220 |

6. PUBLIC COMMENT

An opportunity for public comment period on the PTC application was provided from February 22, 2008 to March 10, 2008 in accordance with IDAPA 58.01.01.209.01.c. During this time, there was a request for a public comment period on DEQ's proposed action. A public comment period was held from May 3, 2008 to June 2, 2008. No comments were received.

APPENDIX A – AIRS INFORMATION

AIRS/AFS^a FACILITY-WIDE CLASSIFICATION^b DATA ENTRY FORM

Permittee/Facility Name: Western Aircraft Inc.
Facility Location: Boise
AIRS Number: 001- 00220

| AIR PROGRAM POLLUTANT | SIP | PSD | NSPS (Part 60) | NESHAP (Part 61) | MACT (Part 63) | SM80 | TITLE V | AREA CLASSIFICATION |
|--------------------------|-----|-----|--------------------|---------------------|-------------------|------|---------|--|
| | | | | | | | | A-Attainment U-Unclassified N- Nonattainment |
| SO ₂ | | | | | | | | U |
| NO _x | | | | | | | | U |
| CO | | | | | | | | U |
| PM ₁₀ | | B | | | | | B | U |
| PT (Particulate) | | B | | | | | | |
| VOC | | B | | | | | B | U |
| THAP (Total HAPs) | | B | | | | | | |
| | | | APPLICABLE SUBPART | | | | | |
| | | | | | | | | |

^a Aerometric Information Retrieval System (AIRS) Facility Subsystem (AFS)

^b AIRS/AFS Classification Codes:

- A = Actual or potential emissions of a pollutant are above the applicable major source threshold. For HAPs only, class "A" is applied to each pollutant which is at or above the 10 T/yr threshold, or each pollutant that is below the 10 T/yr threshold, but contributes to a plant total in excess of 25 T/yr of all HAPs.
- SM = Potential emissions fall below applicable major source thresholds if and only if the source complies with federally enforceable regulations or limitations.
- B = Actual and potential emissions below all applicable major source thresholds.
- C = Class is unknown.
- ND = Major source thresholds are not defined (e.g., radionuclides).

APPENDIX B – EMISSIONS INVENTORY

| Chemical Calculations | * = not on Toxic Air Pollutant 585 or 586 List | % of ingredient | x weight of chemical | x Rated capacity of spray gun in gal/hr | Emission Level | Below Regulatory Concern (10% of Allowable EL) | Total Emissions in tons per year | Hours of actual spraying of this chemical in hours/per year | Actual Total Emissions |
|---|--|-----------------|----------------------|---|----------------|--|----------------------------------|---|------------------------|
| 3M 1357L Contact Adhesive (6.672 lbs/gal) | | | | | | | | | |
| | *Petroleum Distillate | | | | | | | | |
| | Acetone | 0.30 | 6.67 | 2.80 | 5.60 | Yes - EL is 119 | 24.55 | 654 | 1.83 |
| | Ethyl acetate | 0.15 | 6.67 | 2.80 | 2.80 | No - EL is 42 | 12.27 | 654 | 0.92 |
| | *Polychloroprene | | | | 0.00 | | | 654 | 0.00 |
| | *Magnesium Resinate | | | | 0.00 | | | 654 | 0.00 |
| | Methyl Ethyl Ketone | 0.13 | 6.67 | 2.80 | 2.43 | Yes - EL is 39.3 | 10.63 | 654 | 0.79 |
| | Toluene | 0.07 | 6.67 | 2.80 | 1.31 | Yes - EL is 25 | 5.73 | 654 | 0.43 |

1.34

| | | | | | | | | | |
|--|------------------------------------|------|------|------|------|------------------|-------|-----|------|
| Permacron MS Clearcoat 8180 (8.02 lbs/gal) | | | | | | | | | |
| | *Acrylic Resin | | | | 0.00 | | | 654 | 0.00 |
| | Butyl acetate | 0.03 | 8.02 | 2.80 | 0.67 | Yes - EL is 47.3 | 2.95 | 654 | 0.22 |
| | *Ethyl 3-ethoxy propionate | | | | 0.00 | | | 654 | 0.00 |
| | Ethylbenzene | 0.11 | 8.02 | 2.80 | 2.47 | Yes - EL is 29 | 10.82 | 654 | 0.81 |
| | *Ethylene glycol monobutyl acetate | | | | 0.00 | | | 654 | 0.00 |

0.81

| | | | | | | | | | |
|--|--|------|------|------|------|-----------------|-------|-----|------|
| Permasolid HS Hardener 3309 Extra Fast (8.33 lb/gal) | | | | | | | | | |
| | | | | | 0.00 | | | | 0.00 |
| | *1,2,4-trimethyl benzene | | | | 0.00 | | | 654 | 0.00 |
| | *1,3,5-trimethyl benzene | | | | 0.00 | | | 654 | 0.00 |
| | *Aliphatic polyisocyanate resin | | | | 0.00 | | | 654 | 0.00 |
| | *Aromatic hydrocarbon-B | | | | 0.00 | | | 654 | 0.00 |
| | Butyl acetate | 0.27 | 8.33 | 2.80 | 6.30 | No - EL is 47.3 | 27.58 | 654 | 2.06 |
| | Ethylbenzene | 0.02 | 8.33 | 2.80 | 0.47 | Yes - EL is 29 | 2.04 | 654 | 0.15 |
| | *Propylene glycol monomethyl ether acetate | | | | 0.00 | | | 654 | 0.00 |
| | Xylene | 0.07 | 8.33 | 2.80 | 1.63 | Yes - EL is 29 | 7.15 | 654 | 0.53 |

0.69

| | | | | | | | | | |
|---|---------------------------------|------|------|------|------|----------------|------|-----|------|
| Permasolid HS Hardener 3307 Express (8.24 lb/gal) | | | | | | | | | |
| | | | | | | | | | 0.00 |
| | *Aliphatic polyisocyanate resin | | | | 0.00 | | | 654 | 0.00 |
| | *Aromatic hydrocarbon-B | | | | 0.00 | | | 654 | 0.00 |
| | Butyl acetate | 0.00 | 8.24 | 2.80 | 0.00 | | | 654 | 0.00 |
| | Ethylbenzene | 0.01 | 8.24 | 2.80 | 0.18 | Yes - EL is 29 | 0.81 | 654 | 0.06 |

| Chemical Calculations | * = not on Toxic Air Pollutant 585 or 586 List | % of ingredient | x weight of chemical | x Rated capacity of spray gun in gal/hr | Emission Level | Below Regulatory Concern (10% of Allowable EL) | Total Emissions in tons per year | Hours of actual spraying of this chemical in hours/per year | Actual Total Emissions |
|-----------------------|---|--------------------|-------------------------|--|-------------------|--|---|--|---------------------------|
| Total | | | | | | | | | |
| Acetone | | | | | 9.67 | | | Total Acetone | 3.16 |
| Total Ethyl | | | | | | | | Total Ethyl | |
| Benzene | | | | | 3.9 | | | Benzene | 1.27 |

Total HAPs 8.59

Above totals represent emission estimates for all chemicals sprayed for 654 hours.

Emission Level (lb/hr) = % of ingredient (%) * % weight of chemical * rated capacity of spray gun (gal/hr)

Total Emissions (T/yr) = Emission Level (lb/hr) * 8760 hours operation per year
= represents uncontrolled annual emission rate

Actual Total Emission (T/yr) = Emission Level (lb/hr) * Hours of Actual Spraying of this chemical (hr/yr)
= represents emission rate at requested annual hours of operation limit of 654 hr/yr

Permasolid HS Hardener 3307 Express represents worst case annual HAP emission rate at 654 hrs/yr of operation.

| Name/Item Number | Material Coated | Solid lb/gal. | * max rate of spray gun | * % spray gun efficiency | * % spray booth filter efficiency | * Hours of Operation | lbs/hour | TPY | MSDS Attached? |
|---|-----------------|---------------|-------------------------|--------------------------|-----------------------------------|----------------------|----------|------------|----------------|
| Spies Hecker Permacron MS Clear Coat 8180 (29581800) | Wood/Fiberglass | 3.65 | 2.8 | 0.35 | 0.01 | 654 | 0.03577 | 0.01169679 | Yes |
| Spies Hecker Permasolid HS Hardener 3309 Extra Fast (29333091) | Wood/Fiberglass | 0.72 | 2.8 | 0.35 | 0.01 | 654 | 0.007056 | 0.00230731 | Yes |
| Spies Hecker Permasolid HS Hardener 3307 Express (2923307) | Wood/Fiberglass | 3.65 | 2.8 | 0.35 | 0.01 | 654 | 0.03577 | 0.01169679 | Yes |
| Spies Hecker Permasolid HS Hardener 3310 Fast (29133106/29233100) | Wood/Fiberglass | 0.72 | 2.8 | 0.35 | 0.01 | 654 | 0.007056 | 0.00230731 | Yes |
| Spies Hecker Permacron MS Dura Plus 8580 (29585805/29185807) | Wood/Fiberglass | 0.44 | 2.8 | 0.35 | 0.01 | 654 | 0.004312 | 0.00141002 | Yes |
| 3M Scotch-Grip 1357-L High Performance Contact Adhesive | Fabric/Plastic | 0 | 2.8 | 0.35 | 0.01 | 654 | 0 | 0 | Yes |
| Henkel Corp. Hybond 36 (J9831D102) | Fabric/Plastic | 1.05 | 2.8 | 0.35 | 0.01 | 654 | 0.01029 | 0.00336483 | Yes |
| | | | | | | Total | 4578 | 0.100254 | 0.03278306 |

Above totals represent emission estimates for all chemicals sprayed for 654 hours.

lbs/hr = solid (lb/gal)*max rate of spray gun (gal/hr) * % spray gun efficiency (%) * % spray booth filter efficiency
 TPY = lbs/hr * Hours of operation (hours per year) ÷ 2000 lbs/T

| Name/Item Number | Material Coated | VOC Gal. | * max rate of spray gun | * Hours of Operation | Tons per Year | MSDS Attached? |
|---|-----------------|----------|-------------------------|----------------------|---------------|----------------|
| Spies Hecker Permacron MS Clear Coat 8180 (29581800) | Wood/Fiberglass | 4.33 | 2.8 | 654 | 3.96 | Yes |
| Spies Hecker Permasolid HS Hardener 3309 Extra Fast (29333091) | Wood/Fiberglass | 4.33 | 2.8 | 654 | 3.96 | Yes |
| Spies Hecker Permasolid HS Hardener 3307 Express (2923307) | Wood/Fiberglass | 4.3 | 2.8 | 654 | 3.94 | Yes |
| Spies Hecker Permasolid HS Hardener 3310 Fast (29133106/29233100) | Wood/Fiberglass | 4.33 | 2.8 | 654 | 3.96 | Yes |
| Spies Hecker Permacron MS Dura Plus 8580 (29585805/29185807) | Wood/Fiberglass | 7.34 | 2.8 | 654 | 6.72 | Yes |
| 3M Scotch-Grip 1357-L High Performance Contact Adhesive | Fabric/Plastic | 4.08 | 2.8 | 654 | 3.74 | Yes |
| Henkel Corp. Hybond 36 (J9831D102) | Fabric/Plastic | 4.02 | 2.8 | 654 | 3.68 | Yes |
| Worst Case Total VOC | | | | | 6.72 | |

Tons per Year = VOC Gal. (lbs/gal) * max rate of spray gun (gal/hr) * Hours of Operation (hrs/year)

APPENDIX C – MODELING ANALYSIS

(RESERVED)